

Videoscope iRis DVR X

Art.-No.: 1190085



Extremely compact dimensions, minimal weight and optimal handling are the outstanding attributes of the iRis DVR X Videoscope System by Force Ware. Inspections in remote or inaccessible areas of the harsh industrial environments now are feasible in no time and with an undreamed easiness. Only little efforts and iRis DVR is ready for use within seconds. You can move the distal end to any desired position fast, easy and precisely, thanks to the approved tactile 4-way articulation of up to 180°. The high brightness of the LED light source guarantee, that you don't miss any detail on the 5" high resolution TFT display.

The integrated, changeable and rechargeable high power batteries assure 2 hours of operating time. The balanced handle-designed for real-handed operation-allows long and effortless working. With diameters of 4.0 mm and 6.0 mm and lengths from 1.5 m to 7.5 m the iRis DVRX leaves nothing to be desired.

The iRis DVR X Inspection System is a "ready-to-go" Video Kit which includes the iRis DVR X Inspection System specified by articulation, diameter and working length of the following list and all necessary basic accessories, as one battery), Charger, Neck-Holder and Sunshield. It comes in iRis Case (up to 5 m probe length) or iCaseplus (from 6 m probe length, non IATA)

Features

- Xtremely large display
- Xtremely economical
- Xtreme image technology
- Xtreme LED on the tip
- Xtremely fast and easy to use

- Xtremely long battery duration
- Xtremely transportable
- Xtreme 90° Side View Tip Adapter
- Made in Germany





Videoscope iRis DVR X

Art.-No.: 1190085

Specifications

Operating unit

Display size: 5.0" (12.7 cm) TFT colour VGA (640x480 pixel)

Operating system: Real-time operating system, with on-screen menu User interface: Direct action keys / function keys / arrow keys

Languages: English, German, Polish, French, Spanish, Italian, Turkish

Video interface: Composite video-out (BNC)

Power supply, prim.: Rechargeable Li-ion battery (charger and battery included in kit)

Power supply, sec.: 12 V adapter (optional accessory)

Documentation

Video format: MPEG4 (.avi) (with time and date stamp)
Image format: BMP (.bmp) (with time and date stamp)

Storage: SDHC memory card up to 32 GB (FAT32) (8 GB is included in kit)

Camera control

Image sensor: Advanced chip on the tip image sensor

White balance: Factory default or user defined

Image control

Zoom: 16 step digital zoom

Invert: Horizontal and vertical image inversion

Brightness: Adjustable Contrast: Adjustable Colour: Adjustable

Text annotation: Built-in text overlay generator

Illumination

Type: High-power LED (4 mm with fiber optics / 6 mm - LED on the tip)

Illumination control: 3 steps

Colour temperature: approx. 6500 k Average lamp lifetime: approx. 5000 h

Probe

Diameter: 4.0 mm 6.0 mm Working length: (1.5 - 4.0 m) (1.5 - 7.5 m)

Articulation (bending neck): 4-way / 360° control

Integrated objective lens: 90° FOV 90° FOV Yes

Braid: Multi-layer tungsten braid on PU jacket

Construction

Ergonomics: $\pm 90^{\circ}$ rotatable display unit, alt. $\pm 90^{\circ}$ rotatable scope handle

System weight: 1.35 kg

Dimensions: 180 mm x 105 mm x 45 mm

Housing: Rugged PU, with integrated rubber shock caps





Videoscope iRis DVR X Art.-No.: 1190085

Operating environment

Tip operating temperature: -25°C to +80°C System operating temperature: -25°C to +46°C Storage temperature: -25°C to +60°C

Relative humidity: 95% max. - non condensing Waterproof: Probe and distal end up to 1 bar

Resistance: Probe and distal end to oils and saline (5 %) 508 mm x 373 mm x 147 mm / 4,5 kg Carrying Case:

Country of Origin: Germany

Available Models

Model	Probe Diameter (mm)	Probe Lenth (m)	Article No.
iRis DVR X 4-4-150	4	1.5	1190085-01
iRis DVR X 4-4-200	4	2.0	1190085-02
iRis DVR X 4-4-300	4	3.0	1190085-03
iRis DVR X 4-6-150	6	1.5	1190085-04
iRis DVR X 4-6-200	6	2.0	1190085-05
iRis DVR X 4-6-300	6	3.0	1190085-06
iRis DVR X 4-6-400	6	4.0	1190085-07
iRis DVR X 4-6-500	6	5.0	1190085-08
iRis DVR X 4-6-600	6	6.0	1190085-09
iRis DVR X 4-6-750	6	7.5	1190085-10

